

ToxProtect 1402Ex-VarioFix



Manhole – Variable assembly



Part No. 14211 without technology

Part No. 14206 with ULE Ex protection

Part No. 14209 with NB-IoT Ex protection

Part No. 14210 with LoRaWAN Ex protection



Specifications

Material: PP, ABS
Weight: ca. 7400g with VarioFix
Dimensions: Width: ca. 400mm, Height: ca. 800mm
Manhole: DN 800, 1000, 1200, 1500
Ex-protection: Ex II 2G Ex ib IIB T4 Gb
Patent: DE 10 2014 102 034 B4

Use

When used in the sewers, the ToxProtect bait box protects the bait from contact with the water. If the water level rises the ball float floats up and closes the box so that the bait stays dry. It also sends data in relation to the number of visits and records of the bait used to the Webservice.

The rats can feed on the bait inside. If the bait requires to be changed this can be done using a telescopic rod from above (MoveStick).

Assembly

Placed and secured in the manhole chamber from above (MoveStick). 1 person required and process completed in ca. 1 minute. It is suitable for the following standard manholes: DN 800, 1000, 1200 und 1500.

Advantages

- **Assembly/disassembly in ca. 1 min, 1 person**
- **For standard manholes: DN 800, 1000, 1200**
- **One ToxProtect covers an area between 250 – 500 metres**
- **The use of poison is reduced by ca. 90%**

Accessories

MoveStick Part No. 14133

eBox-Grip Part No. 14123

Vario-Grip Part No. 14037



With technology

Reader Part No. 15024

BatteryBox-Grip Part No. 14126

Magnet Part No. 14124

Webservice Part No. 15038

