

ToxProtect 1402Ex–MultiFix



Manhole – Assembled using fixed bracket to chamber walls with variable installation and removal



Part No. 14231 without technology

Part No. 14232 with ULE Ex protection

Part No. 14233 with NB-IoT Ex protection

Part No. 14234 with LoRaWAN Ex protection

Specifications

Material: PP, ABS
Weight: ca. 4200g
Dimensions: Height: ca. 52cm, Diameter: ca. 24cm

Ex-protection: Ex II 2G Ex ib IIB T4 Gb
Patent: DE 10 2014 102 034 B4

Use

The ToxProtect is inserted and removed from the manhole without a requirement to enter. The MultiFix wall bracket is attached to the chamber wall using drilling and remains permanently fixed.

The ToxProtect is lowered into the manhole using the MoveStick and placed into the MultiFix bracket. It remains there securely fixed thanks to the self-locking system.

Assembly


This box is assembled by drilling the MultiFix bracket securely into the chamber wall. The box can then be installed and removed from above using the MoveStick and the built-in self-locking system.

Advantages

- **Entry into the chamber is not required making for easy installation and removal**
- **Maintenance can be carried out safely without entry into the chamber**
- **Can be used in standard and unique manhole chambers (in accordance with box dimensions)**
- **Separate brackets in different locations allows for easy relocation of the box**

Accessories

MoveStick Part No. 14133
eBox-Grip Part No. 14123
Vario-Grip Part No. 14037



With technology

Reader Part No. 15024
BatteryBox-Grip Part No. 14126
Magnet Part No. 14124
WebService Part No. 15038

